

Petra Rozehnalová

Numerical integration in the Trefftz finite element method

In: Jan Chleboun and Pavel Kůs and Petr Přikryl and Karel Segeth and Jakub Šístek and Tomáš Vejchodský (eds.): Programs and Algorithms of Numerical Mathematics, Proceedings of Seminar. Janov nad Nisou, June 19-24, 2016. Institute of Mathematics CAS, Prague, 2017. pp. 97–101.

Persistent URL: <http://dml.cz/dmlcz/703003>

**Terms of use:**

© Institute of Mathematics CAS, 2017

Institute of Mathematics of the Czech Academy of Sciences provides access to digitized documents strictly for personal use. Each copy of any part of this document must contain these *Terms of use*.



This document has been digitized, optimized for electronic delivery and stamped with digital signature within the project *DML-CZ: The Czech Digital Mathematics Library*  
<http://dml.cz>

## NUMERICAL INTEGRATION IN THE TREFFTZ FINITE ELEMENT METHOD

Petra Rozehnalová

Brno University of Technology  
 Veveří 95, Brno, Czech Republic  
 rozehnalova.p@fce.vutbr.cz

**Abstract:** Using the high order Trefftz finite element method for solving partial differential equation requires numerical integration of oscillating functions. This integration could be performed, instead of classic techniques, also by the Levin method with some modifications. This paper shortly describes both the Trefftz method and the Levin method with its modification.

**Keywords:** Trefftz finite element method, Levin method

**MSC:** 65N30, 65D30

### 1. Introduction

The Trefftz finite element method is a method for solving boundary value problems applied already in the 1970. The integrals of oscillating functions often appear during the solving procedure. These integrals can be calculated using the modified Levin method. In this paper we briefly introduce the Trefftz and Levin methods with its necessary modification to be applicable to the Trefftz finite element.

### 2. Trefftz finite element method

Trefftz finite elements are finite elements based on the usage of the auxiliary unknown defined on the edges (faces) of elements that links together the primary unknown defined on each element. This method is described in [1] or [5]. Description of implementation aspect is in [6].

Here, let us briefly present the method on the following model problem. Consider that we are seeking to find the solution of the Laplace equation in a domain  $\Omega \subset \mathbb{R}^2$  endowed with the boundary conditions

$$\begin{aligned} \Delta u &= 0 & \text{in } \Omega, \\ u &= \bar{u} & \text{on } \Gamma_u, \\ \frac{\partial u}{\partial n} &= \bar{q} & \text{on } \Gamma_q, \end{aligned} \tag{1}$$

where  $\bar{u}, \bar{q}$  are known functions, and  $n$  is the normal to the boundary  $\Gamma = \Gamma_u \cup \Gamma_q$ .

Let the domain  $\Omega$  be divided into elements; and over each element  $\Omega_e$ , we assume the function  $u$  in the form

$$u = \sum_{j=1}^M c_j N_j \quad \text{on element } \Omega_e,$$

where  $c_j$  are unknown constants and  $N_j$  are known functions to be chosen such that

$$\Delta N_j = 0 \quad \text{in element } \Omega_e, \text{ for } j = 1, 2, \dots, M.$$

It can be shown that this equation is satisfied by any of the following functions:

$$1, r \cos \theta, r \sin \theta, \dots, r^m \cos m\theta, r^m \sin m\theta, \dots, \quad (2)$$

where  $r$  and  $\theta$  are a pair of polar coordinates.

Let us introduce an auxiliary function  $\tilde{u}$  defined on element boundary only:

$$\tilde{u} = \sum_{i=1}^N d_i \tilde{N}_i,$$

where  $d_i$  stands for nodal displacement and  $\tilde{N}_i$  are standard shape functions.

Let us denote  $q = \frac{\partial u}{\partial n}$  and  $q_1 = \frac{\partial u}{\partial x_1}, q_2 = \frac{\partial u}{\partial x_2}$ . Following the approach in [5], let us introduce the functional  $\Psi_e$ ,

$$\begin{aligned} \Psi_e = \frac{1}{2} \int_{\Omega_e} q_1^2 + q_2^2 d\Omega - \int_{\Gamma_e} q \tilde{u} d\Gamma + \int_{\Gamma_{eq}} \bar{q} \tilde{u} d\Gamma = \\ \frac{1}{2} \int_{\Gamma_e} q u d\Gamma - \int_{\Gamma_e} q \tilde{u} d\Gamma + \int_{\Gamma_{eq}} \bar{q} \tilde{u} d\Gamma, \end{aligned} \quad (3)$$

where  $\Gamma_e$  is the boundary of the element  $\Omega_e$  and  $\Gamma_{eq} = \Gamma_e \cap \Gamma_q$ . The minimalization of the variational functional  $\Psi_e$  for the all elements provides the solution of (1).

### 3. Levin method

The Levin method is an effective way for the numerical integration of rapidly oscillating functions. It is described in [2] for one- and two-dimensional integrals; more details, numerical examples, and error analysis are provided in [3], [4].

Let us briefly introduce this method. The integration problem is transformed into an ordinary differential equation problem to be numerically solved by for example the collocation method.

We consider integrals of the form

$$I = \int_a^b f^t \cdot w dx, \quad (4)$$

where  $f$  is a vector of smooth and non-oscillating functions,  $f(x) = (f_1(x), \dots, f_m(x))^t$ ,  $w$  is a vector of oscillating functions,  $w(x) = (w_1(x), w_2(x), \dots, w_m(x))^t$ , and  $a, b$  are real and finite. We also assume that  $w$  satisfies

$$w'(x) = A(x) w(x),$$

where  $A$  is an  $m \times m$  matrix of non-oscillating functions.

We would like to find the vector  $p(x) = (p_1(x), p_2(x), \dots, p_m(x))^t$  such that

$$(p^t \cdot w)' = f^t \cdot w.$$

Subsequently,

$$\begin{aligned} I = \int_a^b (p^t \cdot w)' dx &= \int_a^b (p')^t \cdot w + p^t \cdot w' dx = \int_a^b (p')^t \cdot w + p^t \cdot A w dx = \\ &= \int_a^b (p' + A^t p)^t \cdot w dx, \end{aligned}$$

Hence, the vector  $p$  should satisfy

$$p' + A^t p = f.$$

Then, the integral is computed as

$$\int_a^b f^t \cdot w dx = p^t(b) \cdot w(b) - p^t(a) \cdot w(a). \quad (5)$$

**Example** As an example, let us compute the integral

$$\int_0^{2\pi} x^2 \cos(rx) dx = \int_0^{2\pi} (x^2, 0) \cdot (\cos(rx), \sin(rx)) dx,$$

where  $r \in \odot \mathbb{N}$ . In the notation used above,  $f(x) = (x^2, 0)^t$  and  $w(x) = (\cos(rx), \sin(rx))^t$ .

Then,

$$w'(x) = \begin{bmatrix} \cos(rx) \\ \sin(rx) \end{bmatrix}' = \begin{bmatrix} 0 & -r \\ r & 0 \end{bmatrix} \begin{bmatrix} \cos(rx) \\ \sin(rx) \end{bmatrix} = A(x) w(x).$$

We are looking for the vector  $p = (p_1, p_2)$  which satisfies

$$\begin{aligned} p'_1 + r p_2 &= x^2, \\ p'_2 - r p_1 &= 0. \end{aligned}$$

The general solutions are

$$p_1(x) = C_1 \cos(rx) + C_2 \sin(rx) + \frac{2x}{r^2}, \quad (6)$$

$$p_2(x) = C_1 \sin(rx) - C_2 \cos(rx) + \frac{x^2}{r} - \frac{2}{r^3}. \quad (7)$$

The formula (5) is valid for any solution of (6). We choose the solution for which  $C_1 = C_2 = 0$ . Hence,

$$\int_0^{2\pi} x^2 \cos(rx) \, dx = \left[ \left( \frac{2x}{r^2}, \frac{x^2}{r} - \frac{2}{r^3} \right) \cdot (\cos(rx), \sin(rx))^t \right]_0^{2\pi} = \frac{4\pi}{r^2}.$$

#### 4. Integration in the Trefftz method

Using functions (2) in functional (3) leads to line integrals of oscillating functions.

It depends on the implementation, but it is usual that only values of the integrated function are accessible. In this content, it is obvious that success of Levin method relies on rewriting  $w'$  as  $Aw$ . In this situation, namely, when only values of  $w$  are known, finding matrix  $A$  could be a problem.

The oscillating function  $w$  can be approximated by the trigonometric interpolation polynomial

$$w(x) \doteq a_0 + \sum_{i=1}^n (a_i \cos(\alpha_i x) + b_i \sin(\alpha_i x)),$$

where the coefficients  $a_0, a_i, b_i, i = 1 \dots N$ , can be effectively computed by the discrete fast Fourier transform.

Then, the integral of the form (4) can be approximated by

$$\begin{aligned} I &\doteq \int_a^b f a_0 + \sum_{i=1}^n f (a_i \cos(\alpha_i x) + b_i \sin(\alpha_i x)) \, dx = \\ &a_0 \int_a^b f \, dx + \int_a^b \sum_{i=1}^n f (a_i \cos(\alpha_i x) + b_i \sin(\alpha_i x)) \, dx. \end{aligned}$$

In this form, the integral is suitable for the Levin method.

#### Acknowledgements

This research has been supported by the specific university research project of Brno University of Technology, No. FAST-S-16-3385, in cooperation with the project LO1408 AdMaS UP (Advanced Materials, Structures and Technologies, Ministry of Education, Youth and Sports of the Czech Republic, National Sustainability Programme I).

#### References

- [1] Jirousek, J. and Wróblewski, A.: T-elements: State of the art and future trends. Arch. Comput. Methods Engrg. **3** (1996), 323–434.
- [2] Levin, D.: Procedures for computing one- and two-dimensional integrals of functions with rapid irregular oscillations. Math. Comp. **38** (1982).

- [3] Levin, D.: Fast integration of rapidly oscillatory functions. J. Comput. Appl. Math. **67** (1996).
- [4] Levin, D.: Analysis of a collocation method for integrationg rapidly oscillatory functions. J. Comput. Appl. Math. **78** (1997).
- [5] Qin, Q.: Trefftz finite element method and its applications. Applied Mechanics Reviews **58** (2005).
- [6] Qin, Q. and Wang, H.: *MATLAB and C programming for Trefftz fnite element methods*. CRC Press, 2008.